

Identifier	Company	Test setting	Pro Rev.1+	Type	Size	Pins	RAS	CAS	Refresh Timing	RAS only	CBR	Hidden	Refresh	Remark
M8B1C4256A	Fujitsu	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
GMT71C4256A	Goldstar	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
HMS14256	Hitachi	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
P21014	Intel	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
MT4C4256	Micron	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
MT4C4258	Micron	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 static column, untested
M5M44256	Mitsubishi	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
M5M44258	Mitsubishi	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 static column, untested
MCM514256A	Motorola	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
uPD414256	NEC	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 static column, untested
uPD424256	NEC	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
uPD424258	NEC	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 static column, untested
uPD424268	NEC	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 static column, write-per-bit, untested
AA41M304	NMB Semiconductor	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
M5M514256A	OKI	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
KM44C256A	Samsung	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
LH64256	Sharp	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
LH64258	Sharp	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 static column, untested
HYB514256B	Siemens	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
HYB534256B	Siemens	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
TMS44C256	Texas Instruments	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
TC514256AP	Toshiba	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
V53C104	Vitelco	44256	X	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8
AA4AM204	NMB Semiconductor	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
AA4AM205	NMB Semiconductor	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available, static column mode
HMS14400	Hitachi	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
HMS14410	Hitachi	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
HY514400	Hyundai	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
HYB514400	Siemens	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
SMJ44400	Texas Instruments	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
HMS14400	Toshiba	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
TC514400	Toshiba	custom	external	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 external definition available
SIMM30 256k x 8	-	SIMM30 - 256k x 8	adapter	256k x 8	2097152	30	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 requires adapter
SIMM30 256k Parity	-	SIMM30-P - 256k x 8	adapter	256k x 8	262144	30	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 requires adapter, tests parity bit only, use with "SIMM30 256k x 8"
SIMM30 1024k x 8	-	SIMM30 - 1024k x 8	adapter	1024k x 8	8388608	30	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 requires adapter
SIMM30 1024k Parity	-	SIMM30-P - 1024k x 8	adapter	1024k x 8	1048576	30	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 requires adapter, tests parity bit only, use with "SIMM30 1024k x 8"
SIMM30 4096k x 8	-	-	-	4096k x 8	33554432	30	2048 (A0-A10)	2048 (A0-A10)	2048, 16ms	x	x	x	x	A0-A10 requires adapter, external definition available
SIMM30 4096k Parity	-	-	-	4096k x 8	4194304	30	2048 (A0-A10)	2048 (A0-A10)	2048, 16ms	x	x	x	x	A0-A10 requires adapter, external definition available, tests parity bit only, use with
ZIP16 64k x 1	-	custom	external	64k x 1	65536	16	256 (A0-A7)	256 (A0-A7)	128, 2ms	x	x	x	x	A0-A6 requires adapter, external definition available, untested
ZIP20 64k x 4	-	ZIP20 - 64k x 4	adapter	64k x 4	262144	20	256 (A0-A7)	256 (A0-A7)	256, 4ms	x	x	x	x	A0-A7 requires adapter
ZIP16 256k x 1	-	ZIP16 - 256k x 1	adapter	256k x 1	262144	16	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 requires adapter
ZIP20 256k x 4	-	ZIP20 - 256k x 4	adapter	256k x 4	1048576	20	512 (A0-A8)	512 (A0-A8)	512, 8ms	x	x	x	x	A0-A8 requires adapter, untested
ZIP20 1024k x 1	-	ZIP20 - 1024k x 1	adapter	1024k x 1	1048576	20	1024 (A0-A9)	1024 (A0-A9)	512, 8ms	x	x	x	x	A0-A8 requires adapter
ZIP20 1024k x 4	-	ZIP20 - 1024k x 4	adapter	1024k x 4	4194304	20	1024 (A0-A9)	1024 (A0-A9)	1024, 16ms	x	x	x	x	A0-A9 requires adapter
ZIP20 4096k x 1	-	-	-	4096k x 1	4194304	20	2048 (A0-A10)	2048 (A0-A10)	1024, 16ms	x	x	x	x	A0-A9 requires adapter
HMS3461	Hitachi	custom	external	64k x 4	1048576	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A7 SAM memory (256 x 4) not tested
M8B1461	Fujitsu	custom	external	64k x 4	1048576	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A7 SAM memory (256 x 4) not tested
MT42C4064	Micron	custom	external	64k x 4	1048576	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A7 SAM memory (256 x 4) not tested
uPD41264	NEC	custom	external	64k x 4	1048576	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A7 SAM memory (256 x 4) not tested
TMS4461	Texas Instruments	custom	external	64k x 4	1048576	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A7 SAM memory (256 x 4) not tested
MT4067-P	Micron	custom	external	64k x 4	262144	20	256 (A0-A7)	256 (A0-A7)	256, 4ms	x	x	x	x	A0-A7
MT1259-P	Micron	custom	external	256k x 1	262144	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A8 not compatible with MT1259 (without "P")
EDH41512 (Module 1)	Electronic Designs	custom	external	2x 256k x 1	524288	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A8
EDH41512 (Module 2)	Electronic Designs	custom	external	2x 256k x 1	524288	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A8
EDH42256	Electronic Designs	custom	external	256k x 2	524288	18	256 (A0-A8)	256 (A0-A8)	256, 4ms	x	x	x	x	A0-A8
D2105	Intel	-	-	1k x 1	1024	18	-	-	-	x	-	-	-	A0-A9 Vdd=17(12V), Vbb=10(0V), Vss=11(-5V), RFSH=5
1103	Intel	-	-	1k x 1	1024	18	-	-	32, 2ms	x	-	-	-	A0-A9 Vss=17(16V), Vbb=10(19V), Vdd=11(0V), PRECHARGE=5
1103A	Intel	-	-	1k x 1	1024	18	-	-	32, 2ms	x	-	-	-	A0-A9 Vss=17(16V), Vbb=10(19V), Vdd=11(0V)
U253	(DDR)	-	-	1k x 1	1024	18	-	-	10us	x	-	-	-	A0-A9 Vss=17(16V), Vbb=10(19V), Vdd=11(0V) = 1103A
MIM4262	National	-	-	2k x 1	2048	22	-	-	32, 1ms	x	-	-	-	A0-A4 Vbb=1, Vss=20, Vdd=5 (8.5/5/-15V)
MMS262	National	-	-	2k x 1	2048	22	-	-	32, 2ms	x	-	-	-	A0-A4 Vbb=1, Vss=20, Vdd=5 (8.5/5/-15V)
M5M514221	OKI	-	-	256k+120 x 4	1049052	16	-	-	-	-	-	-	-	Field Memory
uPD4168	NEC	-	-	8k x 8	65536	28	-	-	-	-	-	-	-	XRAM (refresh=1)
uPD42101	NEC	-	-	910 x 8	7280	24	-	-	-	-	-	-	-	Line Buffer für NTSC TV

gray = tested with chip (or compatible)
green = implemented in Chip Tester
yellow = untested
red = not yet implemented or not possible to implement
(X) = could not be tested with working sample yet
"external" = external definition available (custom ic)